

Western Saw
Quality, Service and
Performance since 1930



Diamond Cores,
Saw Bodies, Tubes
and Laser Technology

3200 Camino Del Sol * Oxnard, CA 93030-8998 * (805) 981-0999 * (800) 388-SAWS * Fax (805) 981-0989

Tube with Lightweight Inner Ring & Spoke Back

Patent # 6,890,132

Diameter x Length	Part#	Weight
10" X 15"	42-100120145-2	25.9 lb
12" X 16"	42-120120155-2	31.1 lb
13" X 17"	42-130120165-2	35.1 lb
14" X 18"	42-140120175-2	39.3 lb
15" X 19"	42-150120185-2	43.7 lb
16" X 20"	42-160120195-2	48.5 lb
18" X 22"	42-180134215-2	64.2 lb

Tube OD	24" Length 23.5" Inside Length		36" Length 35.5" Inside Length		48" Length 47.5" Inside Length		60" Length 59.5" Inside Length		Tube OD
	Part #	Weight	Part #	Weight	Part #	Weight	Part #	Weight	
10	42-100120235-2	34.5 lb	42-100120355-2	46.9 lb	42-100120475-2	59.4 lb	42-100120595-2	71.8 lb	10
12	42-120120235-2	41.4 lb	42-120120355-2	56.3 lb	42-120120475-2	71.2 lb	42-120120595-2	86.1 lb	12
13	42-130120235-2	44.9 lb	42-130120355-2	61.0 lb	42-130120475-2	77.2 lb	42-130120595-2	93.3 lb	13
14	42-140120235-2	48.4 lb	42-140120355-2	65.8 lb	42-140120475-2	83.2 lb	42-140120595-2	100.5 lb	14
15	42-150120235-2	52.0 lb	42-150120355-2	70.6 lb	42-150120475-2	89.2 lb	42-150120595-2	107.8 lb	15
16	42-160120235-2	55.5 lb	42-160120355-2	75.4 lb	42-160120475-2	95.3 lb	42-160120595-2	115.1 lb	16
18	42-180134235-2	68.9 lb	42-180134355-2	93.7 lb	42-180134475-2	118.6 lb	42-180134595-2	143.4 lb	18
20	42-200134235-2	77.0 lb	42-200134355-2	104.6 lb	42-200134475-2	132.2 lb	42-200134595-2	159.8 lb	20
22	42-220134235-2	85.1 lb	42-220134355-2	115.5 lb	42-220134475-2	145.9 lb	42-220134595-2	176.3 lb	22
24	42-240134235-2	93.5 lb	42-240134355-2	126.6 lb	42-240134475-2	159.7 lb	42-240134595-2	192.9 lb	24
25	42-250134235-2	97.7 lb	42-250134355-2	132.2 lb	42-250134475-2	166.7 lb	42-250134595-2	201.2 lb	25
26	42-260134235-2	101.9 lb	42-260134355-2	137.8 lb	42-260134475-2	173.7 lb	42-260134595-2	209.6 lb	26
27	42-270134235-2	106.2 lb	42-270134355-2	143.5 lb	42-270134475-2	180.7 lb	42-270134595-2	218.0 lb	27
28	42-280134235-2	110.5 lb	42-280134355-2	149.1 lb	42-280134475-2	187.8 lb	42-280134595-2	226.5 lb	28
29	42-290134235-2	114.8 lb	42-290134355-2	154.9 lb	42-290134475-2	194.9 lb	42-290134595-2	234.9 lb	29
30	42-300134235-2	119.2 lb	42-300134355-2	160.6 lb	42-300134475-2	202.0 lb	42-300134595-2	243.4 lb	30
31	42-310134235-2	148.4 lb	42-310134355-2	191.2 lb	42-310134475-2	234.0 lb	42-310134595-2	276.8 lb	31
32	42-320134235-2	153.6 lb	42-320134355-2	197.7 lb	42-320134475-2	241.9 lb	42-320134595-2	286.1 lb	32
33	42-330134235-2	158.8 lb	42-330134355-2	204.3 lb	42-330134475-2	249.9 lb	42-330134595-2	295.5 lb	33
34	42-340134235-2	164.0 lb	42-340134355-2	210.9 lb	42-340134475-2	257.9 lb	42-340134595-2	304.8 lb	34
35	42-350134235-2	170.2 lb	42-350134355-2	218.5 lb	42-350134475-2	266.8 lb	42-350134595-2	315.1 lb	35
36	42-360134235-2	175.4 lb	42-360134355-2	225.1 lb	42-360134475-2	274.8 lb	42-360134595-2	324.5 lb	36
38	42-380134235-2	186.8 lb	42-380134355-2	239.3 lb	42-380134475-2	291.7 lb	42-380134595-2	344.2 lb	38
40	42-400134235-2	198.2 lb	42-400134355-2	253.4 lb	42-400134475-2	308.7 lb	42-400134595-2	363.9 lb	40
42	42-420134235-2	209.6 lb	42-420134355-2	267.6 lb	42-420134475-2	325.6 lb	42-420134595-2	383.6 lb	42
44	42-440134235-2	221.1 lb	42-440134355-2	281.8 lb	42-440134475-2	342.5 lb	42-440134595-2	403.3 lb	44
46	42-460134235-2	232.5 lb	42-460134355-2	296.0 lb	42-460134475-2	359.5 lb	42-460134595-2	423.0 lb	46
48	42-480134235-2	244.9 lb	42-480134355-2	311.1 lb	42-480134475-2	377.4 lb	42-480134595-2	443.7 lb	48
50	42-500134235-2	257.3 lb	42-500134355-2	326.3 lb	42-500134475-2	395.4 lb	42-500134595-2	464.4 lb	50
52	42-520134253-2	269.7 lb	42-520134355-2	341.5 lb	42-520134253-2	413.3 lb	42-520134253-2	485.1 lb	52
54	42-540134235-2	282.1 lb	42-540134355-2	356.7 lb	42-540134475-2	431.2 lb	42-540134595-2	505.8 lb	54
56	42-560134235-2	295.5 lb	42-560134355-2	372.8 lb	42-560134475-2	450.2 lb	42-560134595-2	527.5 lb	56
58	42-580134235-2	309.0 lb	42-580134355-2	389.0 lb	42-580134475-2	469.1 lb	42-580134595-2	549.2 lb	58
60	42-600134235-2	322.4 lb	42-600134355-2	405.2 lb	42-600134475-2	488.0 lb	42-600134595-2	570.9 lb	60
62	42-620134235-2	335.8 lb	42-600134355-2	421.4 lb	42-620134475-2	507.0 lb	42-620134595-2	592.6 lb	62
64	42-640134235-2	349.2 lb	42-600134355-2	437.5 lb	42-640134475-2	525.9 lb	42-640134595-2	614.3 lb	64
66	42-660134235-2	361.6 lb	42-600134355-2	452.7 lb	42-660134475-2	543.8 lb	42-660134595-2	635.0 lb	66
68	42-680134235-2	375.0 lb	42-600134355-2	468.9 lb	42-680134475-2	562.8 lb	42-680134595-2	656.7 lb	68
70	42-700134235-2	388.4 lb	42-600134355-2	485.1 lb	42-700134475-2	581.7 lb	42-700134595-2	678.4 lb	70
72	42-720134235-2	401.8 lb	42-600134355-2	501.3 lb	42-720134475-2	600.7 lb	42-720134595-2	700.1 lb	72

10" - 16" Wall Thickness .120" +.004"/-.004"

17" & Up" Wall Thickness .134" +.004"/-.004"

OD Tolerance +.010"/-.010"

Tube Material - 1008 Cold Rold Steel

Bolt on Lightweight Spoke adapter included

Tube Type - Rolled and Welded

F.O.B. (Western Saw - Oxnard, CA)