



3200 Camino Del Sol * Oxnard, CA 93030-8998 * (805) 981-0999 * (800) 388-SAWS * Fax (805) 981-0989

ULTRA

Lightweight Tube with Inner Ring & Bolt on SpokeBack Patent # 6,890,132 and Additional International Patents Pending

Diameter x Length	Part#	Inside Length	Weight
14" X 18"	42-140120180-5	15.750"	34 lb
15" X 19"	42-150120190-5	16.750"	39 lb
16" X 20"	42-160120200-5	17.750"	44 lb
18" X 22"	42-180120220-5	19.750"	58 lb

Tube OD	24" Length 21.750" Inside Length		36" Length 33.750" Inside Length		48" Length 45.750" Inside Length		60" Length 57.750" Inside Length		Tube OD
	Part #	Weight	Part #	Weight	Part #	Weight	Part #	Weight	
14"	42-140120240-5	43 lb	42-140120360-5	60 lb	42-140120480-5	78 lb	42-140120600-5	95 lb	14"
15"	42-150120240-5	46 lb	42-150120360-5	65 lb	42-150120480-5	84 lb	42-150120600-5	102 lb	15"
16"	42-160120240-5	50 lb	42-160120360-5	70 lb	42-160120480-5	90 lb	42-160120600-5	110 lb	16"
18"	42-180120240-5	58 lb	42-180120360-5	80 lb	42-180120480-5	102 lb	42-180120600-5	125 lb	18"
20"	42-200120240-5	65 lb	42-200120360-5	90 lb	42-200120480-5	115 lb	42-200120600-5	140 lb	20"
22"	42-220120240-5	73 lb	42-220120360-5	100 lb	42-220120480-5	127 lb	42-220120600-5	155 lb	22"
24"	42-240120240-5	81 lb	42-240120360-5	110 lb	42-240120480-5	140 lb	42-240120600-5	170 lb	24"
25"	42-250120240-5	84 lb	42-250120360-5	115 lb	42-250120480-5	146 lb	42-250120600-5	178 lb	25"
26"	42-260120240-5	88 lb	42-260120360-5	121 lb	42-260120480-5	153 lb	42-260120600-5	185 lb	26"
27"	42-270120240-5	92 lb	42-270120360-5	126 lb	42-270120480-5	159 lb	42-270120600-5	193 lb	27"
28"	42-280120240-5	96 lb	42-280120360-5	131 lb	42-280120480-5	166 lb	42-280120600-5	201 lb	28"
29"	42-290120240-5	100 lb	42-290120360-5	136 lb	42-290120480-5	172 lb	42-290120600-5	208 lb	29"
30"	42-300120240-5	104 lb	42-300120360-5	142 lb	42-300120480-5	179 lb	42-300120600-5	216 lb	30"
31"	42-310120240-5	108 lb	42-310120360-5	147 lb	42-310120480-5	185 lb	42-310120600-5	224 lb	31"
32"	42-320120240-5	113 lb	42-320120360-5	152 lb	42-320120480-5	192 lb	42-320120600-5	232 lb	32"
33"	42-330120240-5	117 lb	42-330120360-5	158 lb	42-330120480-5	199 lb	42-330120600-5	240 lb	33"
34"	42-340120240-5	121 lb	42-340120360-5	163 lb	42-340120480-5	205 lb	42-340120600-5	247 lb	34"
35"	42-350120240-5	125 lb	42-350120360-5	168 lb	42-350120480-5	212 lb	42-350120600-5	255 lb	35"
36"	42-360120240-5	129 lb	42-360120360-5	174 lb	42-360120480-5	219 lb	42-360120600-5	263 lb	36"
38"	42-380120240-5	138 lb	42-380120360-5	185 lb	42-380120480-5	232 lb	42-380120600-5	279 lb	38"
40"	42-400120240-5	146 lb	42-400120360-5	196 lb	42-400120480-5	245 lb	42-400120600-5	295 lb	40"
42"	42-420120240-5	155 lb	42-420120360-5	207 lb	42-420120480-5	259 lb	42-420120600-5	311 lb	42"
44"	42-440120240-5	164 lb	42-440120360-5	218 lb	42-440120480-5	273 lb	42-440120600-5	328 lb	44"
46"	42-460120240-5	173 lb	42-460120360-5	230 lb	42-460120480-5	287 lb	42-460120600-5	344 lb	46"
48"	42-480120240-5	182 lb	42-480120360-5	241 lb	42-480120480-5	301 lb	42-480120600-5	360 lb	48"
50"	42-500120240-5	191 lb	42-500120360-5	253 lb	42-500120480-5	315 lb	42-500120600-5	377 lb	50"
52"	42-520120240-5	200 lb	42-520120360-5	264 lb	42-520120480-5	329 lb	42-520120600-5	393 lb	52"
54"	42-540120240-5	209 lb	42-540120360-5	276 lb	42-540120480-5	343 lb	42-540120600-5	410 lb	54"
56"	42-560120240-5	219 lb	42-560120360-5	288 lb	42-560120480-5	358 lb	42-560120600-5	427 lb	56"
58"	42-580120240-5	228 lb	42-580120360-5	300 lb	42-580120480-5	372 lb	42-580120600-5	444 lb	58"
60"	42-600120240-5	238 lb	42-600120360-5	312 lb	42-600120480-5	387 lb	42-600120600-5	461 lb	60"
62"	42-620120240-5	247 lb	42-620120360-5	324 lb	42-620120480-5	401 lb	42-620120600-5	478 lb	62"
64"	42-640120240-5	257 lb	42-640120360-5	337 lb	42-640120480-5	416 lb	42-640120600-5	496 lb	64"
66"	42-660120240-5	267 lb	42-660120360-5	349 lb	42-660120480-5	431 lb	42-660120600-5	513 lb	66"
68"	42-680120240-5	277 lb	42-680120360-5	362 lb	42-680120480-5	446 lb	42-680120600-5	530 lb	68"
70"	42-700120240-5	287 lb	42-700120360-5	374 lb	42-700120480-5	461 lb	42-700120600-5	548 lb	70"
72"	42-720120240-5	297 lb	42-720120360-5	387 lb	42-720120480-5	476 lb	42-720120600-5	566 lb	72"
74"	42-740134240-5	328 lb	42-740134360-5	430 lb	42-740134480-5	533 lb	42-740134600-5	635 lb	74"
76"	42-760134240-5	339 lb	42-760134360-5	444 lb	42-760134480-5	549 lb	42-760134600-5	654 lb	76"
78"	42-780134240-5	350 lb	42-780134360-5	457 lb	42-780134480-5	565 lb	42-780134600-5	673 lb	78"
80"	42-800134240-5	360 lb	42-800134360-5	471 lb	42-800134480-5	581 lb	42-800134600-5	692 lb	80"
82"	42-820134240-5	371 lb	42-820134360-5	484 lb	42-820134480-5	597 lb	42-820134600-5	711 lb	82"
84"	42-840134240-5	382 lb	42-840134360-5	498 lb	42-840134480-5	614 lb	42-840134600-5	730 lb	84"
86"	42-860134240-5	392 lb	42-860134360-5	511 lb	42-860134480-5	630 lb	42-860134600-5	749 lb	86"
88"	42-880134240-5	403 lb	42-880134360-5	525 lb	42-880134480-5	646 lb	42-880134600-5	768 lb	88"
90"	42-900134240-5	414 lb	42-900134360-5	538 lb	42-900134480-5	662 lb	42-900134600-5	787 lb	90"
92"	42-920134240-5	425 lb	42-920134360-5	552 lb	42-920134480-5	679 lb	42-920134600-5	806 lb	92"
94"	42-940134240-5	435 lb	42-940134360-5	565 lb	42-940134480-5	695 lb	42-940134600-5	825 lb	94"
96"	42-960134240-5	446 lb	42-960134360-5	578 lb	42-960134480-5	711 lb	42-960134600-5	843 lb	96"
98"	42-980134240-5	457 lb	42-980134360-5	592 lb	42-980134480-5	727 lb	42-980134600-5	863 lb	98"

31" OD and Down 6 Spokes, 2.0" Hex with 1-1/4"-7 Thread 32" OD and Up 8 Spokes, 2.5" Hex with 1-1/4"-7 Thread

Standard Wall Thickness .120" +.004"/-.004" up to 72", Optional Wall Thickness .134" +.004"/-.004" Add 3%, Optional Wall Thickness .187" +.004"/-.004" Add 10%

OD Tolerance +.010"/-.010" Tube Material - 1008 Cold Rolled Steel Bolt on Lightweight Spoke adapter included Tube Type - Rolled and Welded