



3200 Camino Del Sol * Oxnard, CA 93030-8998 * (805) 981-0999 * (800) 388-SAWS * Fax (805) 981-0989

ULTRA-X2

Lightweight Tube with Inner Ring & Bolt on SpokeBack
X-Changeable Nut System + A Flange

Patent # 6,890,132 and Additional International Patents Pending

Diameter x Length	Part#	Inside Length	Weight
14" X 18"	42-140120180-7	15.750"	34 lb
15" X 19"	42-150120190-7	16.750"	39 lb
16" X 20"	42-160120200-7	17.750"	44 lb
18" X 22"	42-180120220-7	19.750"	58 lb

Tube OD	24" Length 21.750" Inside Length		36" Length 33.750" Inside Length		48" Length 45.750" Inside Length		60" Length 57.750" Inside Length		Tube OD
	Part #	Weight	Part #	Weight	Part #	Weight	Part #	Weight	
14"	42-140120240-7	43 lb	42-140120360-7	60 lb	42-140120480-7	78 lb	42-140120600-7	95 lb	14"
15"	42-150120240-7	46 lb	42-150120360-7	65 lb	42-150120480-7	84 lb	42-150120600-7	102 lb	15"
16"	42-160120240-7	50 lb	42-160120360-7	70 lb	42-160120480-7	90 lb	42-160120600-7	110 lb	16"
18"	42-180120240-7	58 lb	42-180120360-7	80 lb	42-180120480-7	102 lb	42-180120600-7	125 lb	18"
20"	42-200120240-7	65 lb	42-200120360-7	90 lb	42-200120480-7	115 lb	42-200120600-7	140 lb	20"
22"	42-220120240-7	73 lb	42-220120360-7	100 lb	42-220120480-7	127 lb	42-220120600-7	155 lb	22"
24"	42-240120240-7	81 lb	42-240120360-7	110 lb	42-240120480-7	140 lb	42-240120600-7	170 lb	24"
25"	42-250120240-7	84 lb	42-250120360-7	115 lb	42-250120480-7	146 lb	42-250120600-7	178 lb	25"
26"	42-260120240-7	88 lb	42-260120360-7	121 lb	42-260120480-7	153 lb	42-260120600-7	185 lb	26"
27"	42-270120240-7	92 lb	42-270120360-7	126 lb	42-270120480-7	159 lb	42-270120600-7	193 lb	27"
28"	42-280120240-7	96 lb	42-280120360-7	131 lb	42-280120480-7	166 lb	42-280120600-7	201 lb	28"
29"	42-290120240-7	100 lb	42-290120360-7	136 lb	42-290120480-7	172 lb	42-290120600-7	208 lb	29"
30"	42-300120240-7	104 lb	42-300120360-7	142 lb	42-300120480-7	179 lb	42-300120600-7	216 lb	30"
31"	42-310120240-7	108 lb	42-310120360-7	147 lb	42-310120480-7	185 lb	42-310120600-7	224 lb	31"
32"	42-320120240-7	113 lb	42-320120360-7	152 lb	42-320120480-7	192 lb	42-320120600-7	232 lb	32"
33"	42-330120240-7	117 lb	42-330120360-7	158 lb	42-330120480-7	199 lb	42-330120600-7	240 lb	33"
34"	42-340120240-7	121 lb	42-340120360-7	163 lb	42-340120480-7	205 lb	42-340120600-7	247 lb	34"
35"	42-350120240-7	125 lb	42-350120360-7	168 lb	42-350120480-7	212 lb	42-350120600-7	255 lb	35"
36"	42-360120240-7	129 lb	42-360120360-7	174 lb	42-360120480-7	219 lb	42-360120600-7	263 lb	36"
38"	42-380120240-7	138 lb	42-380120360-7	185 lb	42-380120480-7	232 lb	42-380120600-7	279 lb	38"
40"	42-400120240-7	146 lb	42-400120360-7	196 lb	42-400120480-7	245 lb	42-400120600-7	295 lb	40"
42"	42-420120240-7	155 lb	42-420120360-7	207 lb	42-420120480-7	259 lb	42-420120600-7	311 lb	42"
44"	42-440120240-7	164 lb	42-440120360-7	218 lb	42-440120480-7	273 lb	42-440120600-7	328 lb	44"
46"	42-460120240-7	173 lb	42-460120360-7	230 lb	42-460120480-7	287 lb	42-460120600-7	344 lb	46"
48"	42-480120240-7	182 lb	42-480120360-7	241 lb	42-480120480-7	301 lb	42-480120600-7	360 lb	48"
50"	42-500120240-7	191 lb	42-500120360-7	253 lb	42-500120480-7	315 lb	42-500120600-7	377 lb	50"
52"	42-520120240-7	200 lb	42-520120360-7	264 lb	42-520120480-7	329 lb	42-520120600-7	393 lb	52"
54"	42-540120240-7	209 lb	42-540120360-7	276 lb	42-540120480-7	343 lb	42-540120600-7	410 lb	54"
56"	42-560120240-7	219 lb	42-560120360-7	288 lb	42-560120480-7	358 lb	42-560120600-7	427 lb	56"
58"	42-580120240-7	228 lb	42-580120360-7	300 lb	42-580120480-7	372 lb	42-580120600-7	444 lb	58"
60"	42-600120240-7	238 lb	42-600120360-7	312 lb	42-600120480-7	387 lb	42-600120600-7	461 lb	60"
62"	42-620120240-7	247 lb	42-620120360-7	324 lb	42-620120480-7	401 lb	42-620120600-7	478 lb	62"
64"	42-640120240-7	257 lb	42-640120360-7	337 lb	42-640120480-7	416 lb	42-640120600-7	496 lb	64"
66"	42-660120240-7	267 lb	42-660120360-7	349 lb	42-660120480-7	431 lb	42-660120600-7	513 lb	66"
68"	42-680120240-7	277 lb	42-680120360-7	362 lb	42-680120480-7	446 lb	42-680120600-7	530 lb	68"
70"	42-700120240-7	287 lb	42-700120360-7	374 lb	42-700120480-7	461 lb	42-700120600-7	548 lb	70"
72"	42-720120240-7	297 lb	42-720120360-7	387 lb	42-720120480-7	476 lb	42-720120600-7	566 lb	72"
74"	42-740134240-7	328 lb	42-740134360-7	430 lb	42-740134480-7	533 lb	42-740134600-7	635 lb	74"
76"	42-760134240-7	339 lb	42-760134360-7	444 lb	42-760134480-7	549 lb	42-760134600-7	654 lb	76"
78"	42-780134240-7	350 lb	42-780134360-7	457 lb	42-780134480-7	565 lb	42-780134600-7	673 lb	78"
80"	42-800134240-7	360 lb	42-800134360-7	471 lb	42-800134480-7	581 lb	42-800134600-7	692 lb	80"
82"	42-820134240-7	371 lb	42-820134360-7	484 lb	42-820134480-7	597 lb	42-820134600-7	711 lb	82"
84"	42-840134240-7	382 lb	42-840134360-7	498 lb	42-840134480-7	614 lb	42-840134600-7	730 lb	84"
86"	42-860134240-7	392 lb	42-860134360-7	511 lb	42-860134480-7	630 lb	42-860134600-7	749 lb	86"
88"	42-880134240-7	403 lb	42-880134360-7	525 lb	42-880134480-7	646 lb	42-880134600-7	768 lb	88"
90"	42-900134240-7	414 lb	42-900134360-7	538 lb	42-900134480-7	662 lb	42-900134600-7	787 lb	90"
92"	42-920134240-7	425 lb	42-920134360-7	552 lb	42-920134480-7	679 lb	42-920134600-7	806 lb	92"
94"	42-940134240-7	435 lb	42-940134360-7	565 lb	42-940134480-7	695 lb	42-940134600-7	825 lb	94"
96"	42-960134240-7	446 lb	42-960134360-7	578 lb	42-960134480-7	711 lb	42-960134600-7	843 lb	96"
98"	42-980134240-7	457 lb	42-980134360-7	592 lb	42-980134480-7	727 lb	42-980134600-7	863 lb	98"

29" OD and Down 6 Spokes, 2.0" Hex with 1-1/4"-7 Thread 30" OD and Up 8 Spokes, 2.5" Hex with 1-1/4"-7 Thread

Standard Wall Thickness .120" +.004"/-.004" up to 72", Optional Wall Thickness .134" +.004"/-.004" Add 3%, Optional Wall Thickness .187" +.004"/-.004" Add 10%

OD Tolerance +.010"/-.010" Tube Material - 1008 Cold Rolled Steel Bolt on Lightweight Spoke adapter included Tube Type - Rolled and Welded